

Project Name:	Type:
Product Code:	Date:

VANILLA 4 INCH ADJUSTABLE DOWNLIGHT



Vanilla 4 Inch Adjustable Downlight

The Vanilla product family is a small recessed adjustable downlight providing high visual comfort thanks to a deep recessed LED Engine. Vanilla comes with a modular and tool free LED-engine and optical accessories that are field changeable. Fixture is serviceable through the aperture. The Body is made of high grade Aluminum. The fixture is tilttable vertically 0-32° and rotatable horizontally 355°. Adjustable 32° always inside ceiling level. The fixtures is provided standard with retrofit housing. IC (title 24) housing available as an option for 4 inch version of fixture.



PERFORMANCE

	STATIC WHITE LED	WARM DIM LED
CCT:	2700K / 3000K	1800K - 3000K
CRI:	97 CRI	90 CRI
WATTAGE:	12 WATTS (350 mA)	10 WATTS (350 mA)
LUMENS:	1160 Delivered	1160 Delivered
SDMC:	2 Step	2 Step
CRI:	2700K 3000K	1800K 3000K




BEAM SPREAD




KEY DIMENSIONS


TRIMLESS ROUND




TRIMMED ROUND



TRIMLESS SQUARE



TRIMMED SQUARE




DRIVER SPECIFICATIONS

	STATIC WHITE (E4)	WARM DIM (EW)
DIMMING:	ELV 2 Wire	ELV 2 Wire
LED CLASS:	2 Output	2 Output
AC INPUT	110-277 VAC 0.23 - 0.09A 50/60 HZ	110 - 277 VAC 0.23-0.09A 50/60 Hz
DC OUTPUT:	350mA	350mA
WATTS:	Max 18W	Max 18W

HOUSING SPECIFICATIONS

RETROFIT DRIVE ENCLOSURE SPECS



ELV Standard 2-Wire Dimming



*FOR OTHER DIMMING STYLES CONTACT LGN



TRIM OPTIONS

R4 - ROUND

TRIM TYPE	TL TRIMLESS	TR TRIMMED	FINISH
FX FLAT IP20			 W WHITE
CX CONCAVE IP20			 B BLACK
FH FLAT HEXCELL IP20			 C CUSTOM
FS FLAT SOLITE IP44			

S4 - SQUARE

FX FLAT IP20			
CX CONCAVE IP20			
FH FLAT HEXCELL IP20			
FS FLAT SOLITE IP44			



ORDER INFORMATION

Order Code

VAN	PROFILE	TRIM	TRIM TYPE	FINISH	TEMP	OPTICS	DRIVER	HOUSING		
VAN -	R4 4" ROUND ADJ. S4 4" SQUARE ADJ.	R-TR4 ROUND TRIMMED	FX FLAT -IP20	W WHITE	27-4 2700K	11-4	E4 ELV	RT RETROFIT		
		R-TL4 ROUND TRIMLESS	CX CONCAVE - IP20						B BLACK	30-4 3000K
			S-TR4 SQUARE TRIMMED	FH FLAT HEXCELL -IP20	C CUSTOM *	WD-4 (1800 K - 3000K)	20-4	EW ELV**		
			S-TL4 SQUARE TRIMLESS	FS FLAT SOLITE SHOWER - IP44						30-4
				CS CONCAVE SOLITE SHOWER -IP44						38-4
										60-4

*CUSTOM FINISHES REQUIRE A MINIMUM QUANTITY OF 25 FIXTURES

**OTHER DIMMING OPTIONS AVAILABLE UPON REQUEST

*** IC HOUSING REQUIRED FOR JA8 T24 COMPLIANCE

Fixture Components


Housing/Enclosure		<p>Power Source 120 V Connection</p>	<p>Housing/ Enclosure Above ceiling IC housing or Above ceiling RT Retrofit Housing enclosure for ELV driver and line voltage connection</p>	<p>Housing Enclosure Options RT - Retrofit Retrofit housing for all other</p>
Driver		<p>Driver Low Voltage ELV Standard 2 Wire Dimming. Other Dimming Styles available through custom orders. Contact LGN.</p>	<p>IC - Insulated Ceilings IC Housing required for Insulated ceilings. Required IAB T24 Compliance</p>	
Light Source		<p>Light Source LED engine with 3 CCT options. Adjustable gimbal trim allows for aimable spot lighting.</p>		
Optics		<p>Optics Field-interchangeable optic reflectors with spot, narrow flood, and wide flood beam spread options.</p>		

Housing / Retrofit Enclosure Specifications

E4 (4 Inch) Product Data	
RT - Retrofit	IC - Insulated Ceiling Housing Enclosure (IC TITLE 24)
Specifications:	Specifications:
Dimensions: 6 1/2 x 1 5/8 x 1 3/8	Dimensions: 8 1/2 x 10 7/8 x 6 7/8
IP Rating: IP 20	IP Rating: IP 20
Light Source: LED	Light Source: LED
AC Input: 110-277 VAC - 0.23-0.09A 50/60 Hz	AC Input: 110-277 VAC - 0.23-0.09A 50/60 Hz
<p>6 1/2" 165.10 mm 1 15/8" 41.26 mm 1 3/8" 34.92 mm E4</p>	<p>10 7/8" 276.23 mm 10 7/8" 276.23 mm 6 7/8" 174.63 mm IC</p>

INSTALLATION GUIDE

Trimless



Trimmed

